

The ultimate solution for demanding situations requiring super capacities in a compact package. Available in six standard offerings with custom design and manufacturing capabilities for an assortment of potential application specific uses. While taking up only 6.5" of vertical clearance, these casters are capable of moving up to 32,000lbs. Heavy duty 1/2" thick reinforced steel construction backed by RWM's proven kingpinless raceway design provide the necessary strength to get the job done right. Ideal for enabling heavy machinery equipment, tooling, die molds, and home manufacturing lines to get the heaviest of loads off the ground and mobile. Custom caster solutions are available and all RWM kingpinless product including the Super Compact casters are produced in the U.S.A.

FEATUR	RES								
						available with Nylatron H d application specific inp			
Wheel Diameter	Wheel Width	Wheel Type	Capacity		Overall Height	Model #	Swivel Lead	Approx. Weight	
4	4	Machined Steel	10,000 lbs.		6″	SC85-MSB-0440-S	2-1/4″	28 lbs.	
4	4	Machined Steel	32,000 lbs.		6-1/2″	SC125-MSB-0440-S	2-1/4″	47 lbs.	
	Top Plate Information								
	Model Number		per	Top Plate		Plate Dimensions			
		SC85-MSB-044	0-S	Standard		6" x 7" - 4-5/8" x 5/2 slotted to 4-3/8" x 5-5/8"			
				Optional 95ST		6" X 7 1/2" - 4 1/2" X 6" Slotted to 4 1/8" X 6 1/8"			
				Optional LLST		8 1/2" X 11" - 7" X 9 3/4"			
				Optional LMST		8 1/2" X 8 1/2" - 7" X 7"			
		SC125-MSB-044	40-S	Standard		8 1/2" X 8 1/2" - 7" X 7"			
		C85-MSB-0440-S			al LLST	8 1/2" X 11" - 7" X 9 3/4"			
	SC83-INISB	P.O. Box e Phone	668 e: 1-80	1225 Isley 0-634-77	04 Fax:	astonia, NC 28053 1-800-253-6634	MAI IN T U.S	HE	
		WWV	<b>N</b> .I	WII	icas	ters.com		N' R	